GIS GHF & GMF TROLLEYS – 250–6300 KG



GIS GHF and GMF series trolleys are designed especially for use with GIS electric chain hoists. They offer a safe and efficient solution for moving loads. The GHF series covers manual trolleys, while the GMF series offers motorised versions.


GIS





PRODUCT DESCRIPTION

Features

- Wide capacity range: Lifting capacity 250–6300 kg
- Compatibility: Suits GIS GP, GPR, GPK and GPFU series hoists
- Durable construction: Made from high-quality materials that ensure long service life
- Easy installation: Adjustable flange width allows quick and easy installation
- Safety: Equipped with overload protection and other safety features

Technical data

Lifting capacities:

- GHF/GMF 1250: 1250 kg
- GHF/GMF 2500: 2500 kg

- GHF/GMF 4000: 4000 kg
- GHF/GMF 5000: 5000 kg
- GHF/GMF 6300: 6300 kg

Travel speed:

- Manual models: operator-driven
- Motorised models: 12/4 m/min or 24/6 m/min

Flange width:

- GHF/GMF 1250: 70–140 mm or 70–240 mm
- GHF/GMF 2500: 88–200 mm or 88–300 mm
- GHF/GMF 5000/6300: 91–300 mm

Motor types (GMF):

- 3-phase 400 V / 50 Hz
- 1-phase 230 V / 50 Hz

Net weight:

- GHF/GMF 1250: 29–30 kg
- GHF/GMF 2500: 37–38 kg
- GHF/GMF 4000: 54–55 kg
- GHF/GMF 5000: 62–63 kg
- GHF/GMF 6300: 77–78 kg

Model options

- GHF: Manual trolley
- GMF: Motorised trolley
- GMF FU: Motorised trolley with frequency inverter
- GHF/GMF R: Stainless steel trolley
- GHF/GMF EX: Explosion-proof trolley

Applications

- Industry and manufacturing
- Construction
- Logistics and warehousing
- Chemical and food industries
- Hazardous areas (EX models)

Interested? Contact us

Message:

Name (required)

Email (required)

Phone (required)

Company

Recaptcha

Lähetä yhteydenottopyyntö