UNDER-BRACED PILLAR JIB CRANES



PRODUCT DESCRIPTION

Under-braced pillar jib cranes (PKA)

Lifting capacity from 125 kg, special solutions up to 10,000 kg

Applications

Under-braced pillar jib cranes are well suited to industrial and production facilities that need an efficient and flexible lifting solution. They allow loads to be moved over a wide area and offer options for both manual and motorised operation.

Technical features

- Lifting capacity: 125–2000 kg in standard solutions; up to 20,000 kg in special solutions
- Boom: steel I-beam
- Slewing angle: 270° as standard; full rotation as a special design
- Boom slewing: manual
- Hoist trolley travel: manual or motorised
- Power supply: flat cable festoon on a separate C-rail; can be fitted with a pendant control on its own rail
- Mounting: floor; additional support from the top of the column possible on standard cranes

Structure and installation

- Column: robust steel structure that ensures the crane's stability and durability
- Installation: floor mounting; additional support from the top of the column possible on standard cranes
- Finish: durable paint, for example two-component epoxy

Accessories

- Slewing angle limiters: allow the slewing angle to be adjusted as needed

Download the product brochure from the link below:
under-braced, indicative

Interested? Contact us

Message:

Name (required)

Email (required)

Phone (required)

Company

Recaptcha

Lähetä yhteydenottopyyntö