TEKNOWINCH CAPSTAN SERIES 500 – 3000 KG FOR PULLING



Teknowinch Capstan is an electric pulling winch for sites where the load must be pulled in a controlled way without rope winding onto a drum. It suits industrial, maintenance and special applications.

PRODUCT DESCRIPTION

Brake motor as standard. Operated with a foot pedal control.

Many options available:

- drum sized to requirements
- mechanical ratchet wheel
- stainless or acid-resistant construction
- ATEX equipment

For horizontal pulling, max. 3000 kg
Unlimited rope length. Dyneema rope can also be used.
Pulling speeds single-speed 0 – 60 m/min, case by case.
With frequency inverter control, 2-speed or stepless.
Control options: usually a foot switch control.
Standard operating voltages 230/400 V/50 Hz, single- and three-phase. Other voltages case by case.
Also available with hydraulic drive.
Standard protection class IP 55, also IP 56 and IP 66 certified for marine applications.
Standard finish epoxy-painted RAL 5010 blue. Other surface treatments case by case.

Winch quotation request, preliminary winch details:

Application
Lifting winch ▼

Load capacity

Rope length

Speed

Drive
Electric ▼

Control method
Radio control ▼

Operating conditions
Indoor use +10..+40 °C ▼

Special conditions (seawater, chemicals, vapours..)

Finish
Painted ▼

Budget enquiry, we only need an indicative price
☐Preliminary budget enquiry

Message:

Name (required)

Email (required)

Phone (required)

Company

Recaptcha

Lähetä yhteydenottopyyntö