TELECRANE F24-60



Telecrane F24-60+ Joystick is an industrial radio remote control designed especially for remote control of tower cranes, concrete pumps and processing machines. Its dual 5-step joysticks and six single-speed buttons allow precise and versatile control. A durable fibre-reinforced nylon

enclosure and IP65 protection ensure the unit works in demanding industrial environments. In addition, the emergency stop button and rotary key switch improve safety and prevent unauthorised use.



PRODUCT DESCRIPTION

elecrane F24-60+ Joystick is an industrial radio remote control designed especially for remote control of tower cranes, concrete pumps and processing machines. Its ergonomic design and versatile features make it a reliable and efficient tool for demanding industrial applications.

Key features

- **Dual 5-step joysticks**: Allow precise and versatile control.
- **Six single-speed buttons**: Add control options for different functions.
- **Four selector switches**: Two two-position and two three-step switches provide additional configuration options.
- **Emergency stop button (EMS)**: Improves safety in emergencies.
- **Rotary key switch**: Prevents unauthorised use and increases safety.
- **Durable construction**: A fibre-reinforced nylon enclosure provides impact resistance in demanding industrial environments.
- **Wide operating temperature range**: Operates reliably at temperatures from -35°C to +80°C.
- **IP65 protection class**: Protects the unit against dust and water, allowing use in challenging conditions.

Safety and interference prevention

- **SRC (Security Random Code)**: A randomly generated radio code prevents unauthorised copying and use.
- **Hamming coding and CRC (Cyclic Redundancy Check)**: Improve data transmission accuracy and reduce the chance of errors.
- **Unique ID code**: An individual, non-repeating security code prevents incorrect operation and increases operating safety.

Technical data

Transmitter:

- **Dimensions**: 220 x 110 x 90 mm
- **Weight**: 860 g (without batteries)
- **Power supply**: 4 AA batteries (alkaline or rechargeable)

Receiver:

- **Dimensions**: 290 x 230 x 70 mm
- **Weight**: 2200 g (without cables)
- **Power supply**: Available options 24/48/110/220/380 VAC or 12–24 VDC

Applications

Telecrane F24-60+ is especially suited to the following applications:

- **Tower cranes**: Allows precise and safe remote control.
- **Concrete pumps**: Makes concrete pumping more efficient through remote control.
- **Processing machines**: Improves control and safety of production processes.

Interested? Contact us

Message:

Name (required)

Email (required)

Phone (required)

Company

Recaptcha

Lähetä yhteydenottopyyntö