TELECRANE F25



Telecrane F25 is an industrial radio remote control series offering a reliable and safe solution for remote control of various industrial equipment. The series includes models with 6–10 buttons, available in both single-speed (S) and dual-speed (D) versions, allowing precise and versatile

control. A durable, impact-resistant enclosure and IP65 protection ensure the unit works in demanding industrial environments. Programmable functions and remote pairing also allow quick and easy on-site maintenance.




TELECRANE
REMOTE CONTROL
MODEL NO.: F25-10D
S/N:
CH:
(14) COM 3
(15) SOUTH 1S
(16) NORTH 1S
(17) S/N 2S
(18) COM4
(19) R3
(20) COM5
(21) R1 1S
(22) R2 1S
(23) R1/R2 2S
(24) COM6
(25) R3 1S
(26) R4 1S
(27) R3/R4 2S
AC-1 (1)
AC-2 (2)
MAIN-IN (3)
STOP MAIN1
STOP MAIN2
MAIN-OUT (4)
COM 1 (5)
UP 1S (6)
UP 2S (7)
DOWN 1S (8)
DOWN 2S (9)
COM 2 (10)
EAST 1S (11)
WEST 1S (12)
E/W 2S (13)
CE
FC



PRODUCT DESCRIPTION

Telecrane F25 series industrial radio remote controls offer a reliable and safe solution for remote control of various industrial equipment. These controls are designed to withstand demanding conditions and provide a user-friendly experience.

Key features

- **Durable construction**: An impact-resistant enclosure protects the unit in demanding industrial environments.
- **Emergency stop**: The emergency stop control meets the requirements of EN ISO 13849-1 (PL=d), ensuring a high level of safety.
- **Programmable functions**: The user can adapt the functions to suit different applications.
- **Remote pairing**: Allows quick and easy on-site maintenance.
- **Built-in alarm**: The receiver has a pre-installed alarm, reducing the need for additional installations.

Technical data

Transmitter:

- **Dimensions**: 186 x 61 x 51 mm
- **Weight**: Approx. 250 g without batteries
- **Power supply**: 4 AA batteries (alkaline or rechargeable)

Receiver:

- **Dimensions**: 200 x 162 x 107 mm
- **Weight**: Approx. 1550 g without cables
- **Power supply**: Available options 24/48/110/220/380 VAC or 12–24 VDC

Available models

- **F25-6S**: 6 single-speed buttons
- **F25-6D**: 6 dual-speed buttons

- **F25-8S**: 8 single-speed buttons
- **F25-8D**: 8 dual-speed buttons
- **F25-10S**: 10 single-speed buttons
- **F25-10D**: 10 dual-speed buttons

Applications

Telecrane F25 series remote controls are well suited to industrial applications, such as remote control of cranes, winches, conveyor systems and other material handling equipment. Their durable construction and versatile features make them a reliable choice for demanding work environments.

Interested? Contact us

Message:

Name (required)

Email (required)

Phone (required)

Company

Recaptcha

Lähetä yhteydenottopyyntö